

①BK applicator(Mandatory)


BK	1
Model	Mist outlets

1 1 port	
2 2 ports	
1	2

Orifice(※1) Mist outlets

(※1)
Please select BK12 as Mist outlets 2 ports with less quantity of mist than that of BK2 required.
BK21 (Orifices2/port1) is NOT supported.




On/Off Valve (Option) ※2

Blank No valve
 M Manual Valve
S1 100VAC
S2 200VAC
S3 24VDC

(※2)
・ Specification: **2 port valve.**
・ **M** :
#4415 (Stock)


・ **S□** :
#VX220AF type (Not in stock)
Please contact us when solenoid valve offered.

BLLMB
Nozzle (Dedicated nozzle required)


 BLLMB Loc-Line Nozzle with magnet base for BK	Blank standard length (330mm) (20knuckles)	XX customized length (□□mm) (XXknuckles) (※3)
 BLLM6SB Loc-Line Nozzle with M6 stadbase for BK		
 BLL Loc-Line Nozzle for BK (※4)	20 standard length (330mm) (20knuckles)	XX customized length (□□mm) (XXknuckles) (※3)

(※3)Specify number of knuckles(length) when non-standard length is offered. Please contact us detailed specifications.
・ Nozzle length = 14.5mm x(knuckles) +40mm
・ Nozzle length vary on number of knuckles.

(※4)NOTES for BLL
・ BLL offers connection destination because BLL Unit has no magnet or mount kit oneself.
・ Specify number of knuckles (Fill in 20 even standard length offered)

 NBCS12BF Circular saw nozzle for BK (1inlet-2outlets)	 NBBS13BF25 Band saw nozzle for BK (Blade width:25mm)	NN No nozzle
 NBCS22BF Circular saw nozzle for BK (2inlets-2outlets)	 NBBS13BF38 Band saw nozzle for BK (Blade width:38mm)	

②Optional parts

Filter Regulator	How to Fix Applicator	Options
Blank NOT Equipped (Standard)	Blank (※2) (Standard)	SP Special Specification
FR Equipped	 MG Magnets (※2) Mounted by M6-screws	



BK2-BLLMB

Soft nylon tubing(3m)for delivering mist is packed with BK applicator.
Please contact us for inquires of mist tubing length being 3m over required.